

**OILERS**  
GERMAN

# PRODUCT CATALOG

---

---

**MADE IN GERMANY**

GERMAN OILERS, Vogelweidstraße 8, Frankfurt, GERMANY, [www.germanoilers.com](http://www.germanoilers.com)

### **GERMAN OILERS**

Driven by quality – trusted worldwide.

Based in Frankfurt, Germany, we are a globally active company in the lubricants industry, offering premium solutions for automotive, industrial, and agricultural applications. Our portfolio includes high-performance engine oils, gear and hydraulic oils, greases, additives, brake fluids, and winter chemicals – all developed and manufactured in Germany.

What sets us apart? Certified production, strict quality standards, and deep industry know-how built over years of experience. This gives us a competitive edge in global markets – and makes us a trusted partner for customers in over 70 countries.

From product innovation to reliable delivery, we combine German engineering with international vision. Partner with us – and keep your business running smoothly.

## GERMAN OILERS

Range of products

- **Motor Oils**
- **Gear Oils**
- **Hydraulic Oils**
- **Steering Fluids**
- **Motor Cycle Oils**
- **Agricultural Oils**
- **Construction Oils**
- **Greases**
- **Antifreezes**
- **Brake Fluids**
- **Car Care Products**
- **Industrial Oils**
- **Metal Working Oils**
- **Additives**
- **Classic Car Oils**

If you cannot find your desired product or a specific packaging unit in our catalog, please don't hesitate to contact us. We'll be happy to assist you with your request.

[export@germanoilers.com](mailto:export@germanoilers.com)

[info@germanoilers.com](mailto:info@germanoilers.com)

[www.germanoilers.com](http://www.germanoilers.com)

### CAR MOTOR OILS

10008	OILERS SYNT SAE 0W-8	4
10032	OILERS SYNT SAE 0W-12	4
10133	OILERS SYNT SAE 0W-16	4
10007	OILERS SAE 15W-40	5
10145	OILERS SAE 15W-40 CK-4	5
10009	OILERS SYNT SAE 15W-40 GT	5
10067	OILERS SYNT SAE 0W-30	6
10066	OILERS SYNT SAE 0W-30 VO	6
10166	OILERS SYNT SAE 0W-30 S	6
10020	OILERS SYNT SAE 0W-40	7
10041	OILERS SAE 15W-40 X	7
10118	OILERS SYNT SAE 5W-30 SLD	8
10109	OILERS SYNT SAE 5W-30 C1	8
10060	OILERS SYNT SAE 5W-30 FO-RL	8
10011	OILERS SAE 20W-50	9
10125	OILERS SYNT SAE 5W-30 DPF	9
10126	OILERS SYNT SAE 5W-30 DPF-S	9
10121	OILERS SYNT SAE 5W-30 C4	10
10122	OILERS SYNT SAE 5W-30 C4	10
10149	OILERS SYNT SAE 5W-40 MS	11
10068	OILERS SYNT SAE 5W-40	11
10168	OILERS SYNT SAE 5W-40 L	11
10001	OILERS SYNT SAE 5W-40 F	12
10138	OILERS SYNT SAE 5W-40 C3	12
10101	OILERS SYNT SAE 5W-50	13
10042	OILERS SAE 20W-50 GT	13
10058	OILERS SYNT SAE 10W-40	13
10093	OILERS SYNT SAE 10W-40 HC	14
10070	OILERS RACING SYNT SAE 10W-60	14
10130	OILERS SAE 20W-50 X	14
10110	OILERS SAE 40 CI-4	15
10115	OILERS SAE 50 CI-4	15
10016	OILERS SAE 60 CI-4	15

### MOTOR OIL FOR COMMERCIAL VEHICLES

10134	OILERS SYNT SAE 0W-20	16
10135	OILERS SYNT SAE 0W-20 F	16
10136	OILERS SYNT SAE 0W-20 FE	16
10184	OILERS SYNT SAE 10W-30	17
10143	OILERS SYNT SAE 10W-30 CK-4	17
10144	OILERS SYNT SAE 10W-40 CK-4	18
10004	OILERS SYNT SAE 10W-40 HC	18
10028	OILERS SYNT SAE 10W-40 LA	19
10003	OILERS SYNT SAE 10W-40 X	19

### MULTIFUNCTIONAL OILS

13027	OILERS AGRA SAE 10W-30	20
13055	OILERS AGRA SAE 10W-40	20
13014	OILERS AGRA SAE 15W-30	21
13013	OILERS UTTO SAE 10W-30	21
13017	OILERS SAE 30 TO-4	21
13023	OILERS SAE 50 TO-4	22

### MONO-GRADE MOTOR OILS

10015	OILERS SAE 10 HD	23
10022	OILERS SAE 30 HD	23
10012	OILERS SAE 40 HD	23
10040	OILERS SAE 50 HD	24
10186	OILERS SYNT SAE 5W-20	24
10185	OILERS SYNT SAE 5W-30	24
10046	OILERS SYNT SAE 5W-30 LS	25
10021	OILERS SAE 10 GST	25
10052	OILERS SAE 30 GST	25
10047	OILERS SAE 40 GST	26
10091	OILERS SAE 50 GST	26
10023	OILERS SAE 20W-20 GST	26

### MOTOR CYCLE OILS

10032	OILERS 2T-F	27
10030	OILERS 2T-S	27
10031	OILERS 2T-S	27
10049	OILERS 4T-S 10W-40	28
10050	OILERS 4T-M 20W-50	28

### AUTOMATIC TRANSMISSION FLUIDS (ATF)

15011	OILERS ATF 4-0 R	29
15021	OILERS ATF 4-0 F	29
15020	OILERS ATF 9-0	30
15026	OILERS ATF 9-0 F	30
15081	OILERS ATF 9-1 R	31
15091	OILERS ATF 9-1 R	32
15050	OILERS ATF 9-4 R	33
15051	OILERS ATF 9-4 F	33
15060	OILERS ATF 9-5 B	33
15037	OILERS ATF 9-5 B	34
15047	OILERS ATF 9-6 LV R	35
15063	OILERS ATF 9-8	36
15017	OILERS ATF 9-9 F	36
15100	OILERS ATF 10 F	37
15055	OILERS ATF CVT	38
15035	OILERS ATF DSG F	39

## MANUAL TRANSMISSION OILS

15009	OILERS GEAR OIL SAE 75W SYNT	40
15066	OILERS GEAR OIL SAE 75W-80 SYNT	40
15007	OILERS GEAR OIL SAE 75W-90 SYNT TS-4	41
15008	OILERS GEAR OIL SAE 75W-90 SYNT TS	42
15004	OILERS GEAR OIL SAE 75W-90 SYNT LS-5	42
15002	OILERS GEAR OIL SAE 75W-90 SYNT	42
15001	OILERS GEAR OIL SAE 80W-90	43
15003	OILERS GEAR OIL SAE 80W-90 GL-5	43
15006	OILERS GEAR OIL SAE 80W-90 LS-5	43
15000	OILERS GEAR OIL SAE 80W-90 SYNT	44
15005	OILERS GEAR OIL SAE 85W-90 EP	44
15012	OILERS GEAR OIL SAE 75W-140 SYNT	44
15016	OILERS GEAR OIL SAE 85W-140	45
15116	OILERS GEAR OIL SAE 140	45

## HYDRAULIC- AND STEERING FLUIDS

15501	OILERS LH-M PLUS	46
15502	OILERS ZH-M PLUS F SYNT	46
15509	OILERS ZH-M PLUS F SYNT	47

## BRAKE FLUIDS

25119	OILERS BRAKE FLUID DOT 4	48
25114	OILERS BRAKE FLUID DOT 5.1	48

## INDUSTRIAL OILS / HYDRAULIC FLUIDS

13004	OILERS HLP 22	49
13005	OILERS HLP 32	49
13006	OILERS HLP 46	50
13007	OILERS HLP 68	50
13008	OILERS HLP 100	51

## RADIATOR ANTIFREEZE / COOLANTS

11017	OILERS ANTIFREEZE	52
11018	OILERS ANTIFREEZE G	52
11175	OILERS ANTIFREEZE READY MIX -5°C	52
11185	OILERS ANTIFREEZE READY MIX -5°C G	53
11041	OILERS ANTIFREEZE READY MIX -25°C	53
11042	OILERS ANTIFREEZE READY MIX -25°C G	53
11051	OILERS ANTIFREEZE READY MIX -38°C	54
11052	OILERS ANTIFREEZE READY MIX -38°C G	54
11014	OILERS ANTIFREEZE 12 PLUS	55
11145	OILERS ANTIFREEZE READY MIX 12 PLUS -5°C	55
11048	OILERS ANTIFREEZE READY MIX 12 PLUS -25°C	56
11049	OILERS ANTIFREEZE READY MIX 12 PLUS -37°C	56
11013	OILERS ANTIFREEZE GO13	57
11135	OILERS ANTIFREEZE GO13 READY MIX -5°C	57
11061	OILERS ANTIFREEZE GO13 READY MIX -35°C	58

## ADDITIVES

12110	OILERS OCTANE BOOSTER	59
12120	OILERS CETANE BOOSTER	59
12130	OILERS INJECTION CLEANER	59
12140	OILERS ENGINE FLUSH	59
12150	OILERS RADIATOR LEAK STOP	60
12160	OILERS ANTI SMOKE	60
12170	OILERS DPF CLEANER	60
12180	OILERS RADIATOR CLEANER	60
12190	OILERS DIESEL SYSTEM CLEANER	60
12200	OILERS OIL TREATMENT	61
12215	OILERS CATALYST CLEANER	61

## CONTACT

GERMAN OILERS OFFICE FRANKFURT	62
--------------------------------	----

## TRANSPORT

PACKAGING FOR CONTAINERS	63
PACKAGING FOR TRUCKS	63

### OILERS SYNT SAE 0W-8

#### Description

- fully synthetic motor oil
- high shear stability and optimal aging resistance
- rapid oil circulation even at low temperatures
- excellent wear protection
- reduced pollutant emissions and fuel-saving

#### Specification / Recommendation

JASO GLV-1

### No. 10008

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-12

#### Description

- fully synthetic motor oil
- high performance premium lubricant
- for new gasoline engines and hybrid petrol engines from BMW
- optimal functionality of the particle filter
- reduction of NO<sub>x</sub>, CO and particle emissions
- extremely high oxidation stability
- state-of-the-art additive technology for maximum cleaning effect
- improved fuel economy

#### Specification / Recommendation

BMW Longlife-22FE++

### No. 10032

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-16

#### Description

- fully synthetic motor oil
- high performance lubricant
- for many gasoline engines of passenger cars where low viscosity oils are predilected
- excellent lubricity and wear protection
- stable lubrication film
- very good cold starting properties even at low temperatures
- high engine cleanliness
- lowered oil consumption in conjunction with high fuel efficiency

#### Specification / Recommendation

JAPI SQ  
ILSAC GF-7B

### No. 10033

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 15W-40

### Description

- high performance multigrade motor oil
- for gasoline and diesel engines of passenger cars
- lower fuel and oil consumption
- protection against black sludge
- keeps the engine clean
- modern oxidation inhibitors extend service life of the oil
- optimal wear protection cares for long engine life

### Specification / Recommendation

ACEA A3/B4  
API SN/CF  
MB 229.1  
VW 501 01/505 00

## No. 10007

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 15W-40 CK-4

### Description

- high-performance motor oil
- latest generation of low-emission engines
- low SAPS technology
- high shear stability followed by a stable lubrication film under extreme conditions at higher temperatures
- provides excellent fuel economy
- very good oxidation stability

### Specification / Recommendation

ACEA E7/E11  
API CK-4/CJ-4/SN  
API CI-4/CI-4 Plus  
Allison TES 439  
CAT ECF-3  
Cummins CES 20086  
Detroit Diesel DFS93K222  
Detroit Diesel DDC93K222  
Deutz DQC-III-10LA/18LA  
Ford WSS-M2C171-F1  
Jaso DH-2  
John Deere JDQ-78X  
Mack EOS-4.5  
MAN M 3575/M 3775/M 3275  
MB 228.31  
MTU Type 2.1  
Renault VI RLD-3  
Volvo VDS-4.5

## No. 10145

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 15W-40 GT

### Description

- multigrade motor oil
- for gasoline and diesel engines
- protection against black sludge
- protection against thermal oxidation, corrosion and wear
- all seasons oil

### Specification / Recommendation

API SF/CD

## No. 10009

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-30

#### Description

- fully synthetic low friction motor oil
- maximum thermal and mechanical stability
- excellent viscosity temperature / low evaporation loss
- most modern antifriction additives
- reduces fuel consumption
- maximum wear protection / best low temperature
- highly effective dispersant additives
- especially developed for the latest engine generation of VW with extended oil-drain-intervals (WIV) including the pump injection engines

#### Specification / Recommendation

ACEA C3  
API SN  
BMW Longlife-04  
MB 229.51/229.31  
MB 229.52  
Porsche C30  
VW 504 00/507 00

### No. 10067

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-30 VO

#### Description

- fully synthetic motor oil
- high performance premium lubricant
- for new gasoline engines and hybrid petrol engines from BMW
- optimal functionality of the particle filter
- reduction of NOx, CO and particle emissions
- extremely high oxidation stability
- state-of-the-art additive technology for maximum cleaning effect
- improved fuel economy

#### Specification / Recommendation

ACEA A5/B5  
API SL  
Volvo VCC 95200377

### No. 10066

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-30 S

#### Description

- fully synthetic low friction motor oil
- maximum thermal and mechanical stability
- for gasoline engines
- excellent viscosity temperature / low evaporation loss
- most modern antifriction additives
- reduces fuel consumption
- maximum wear protection / best low temperature
- highly effective dispersant additives
- especially developed for the latest engine generation of VW with extended oil-drain-intervals (WIV) including the pump injection engines

#### Specification / Recommendation

API SQ  
Daihatsu  
GM dexos1 Gen 3  
GM 60945-M  
Honda  
ILSAC GF-7A  
Isuzu  
Hyundai  
Kia  
Lexus  
Mazda  
Nissan  
Subaru  
Suzuki  
Toyota

### No. 10166

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 0W-40

### Description

- fully synthetic low friction motor oil
- excellent suitability for all modern gasoline and diesel engines
- especially advisable for turbocharger and direct injection (DI)
- smooth cold start / very good lubrication on high temperatures
- high quality additives for anti-wear properties, dispersant and detergent
- extreme shear stability / high oxidation resistance
- extended engine life / less maintenance-costs/reduced oil and fuel consumption

### Specification / Recommendation

ACEA A3/B4  
 API SN/CF  
 BMW Longlife-01  
 Ford WSS-M2C937-A  
 MB 226.5/229.5  
 Porsche A40  
 Renault RN 0700/0710  
 VW 502 00/505 00

## No. 10020

### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

## OILERS SAE 15W-40 X

### Description

- super high performance diesel (SHPD) motor oil
- multifunctional for diesel and gasoline engines also with turbocharger
- made for passenger cars, trucks, busses, farm and off road equipment
- meets specifications of European, American and Japanese manufacturers
- excellent thermal / oxidative stability
- reduces sludge and deposit built-up
- maximum oil drain intervals due to highest TBN reserves
- best seal and elastomer compatibility
- slow oil ageing even at high temperatures
- all season oil for mixed fleets

### Specification / Recommendation

ACEA E7/E11  
 API CK-4/CJ-4/SN  
 API CI-4/CI-4 Plus  
 Allison TES 439  
 CAT ECF-3  
 Cummins CES 20086  
 Detroit Diesel DFS93K222  
 Detroit Diesel DDC93K222  
 Deutz DQC-III-10LA/18LA  
 Ford WSS-M2C171-F1  
 Jaso DH-2  
 John Deere JDQ-78X  
 Mack EOS-4.5  
 MAN M 3575/M 3775/M 3275  
 MB 228.31  
 MTU Type 2.1  
 Renault VI RLD-3  
 Volvo VDS-4.5

## No. 10041

### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

### OILERS SYNT SAE 0W-30

#### Description

- synthetic high performance motor oil
- four seasons oil for passenger cars with gasoline and diesel engines
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- especially designed for diesel particulate filter (DPF)
- protects environment / low pollution
- high performance additives / optimal wear protection / best motor cleanliness
- excellent thermal oxidation stability
- longer drain intervals at maximum motor protection
- best low temperature properties
- longer operating life of the engine

#### Specification / Recommendation

ACEA C3/C2  
API SP  
API SN PLUS/CF  
BMW Longlife-04  
MB 229.52/229.51/229.31  
Opel GM dexos2  
VW 505 01/502 00/505 00

### No. 10118

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 5W-30 C1

#### Description

- synthetic high performance / low friction motor oil
- for the latest generations of passenger cars and vans with diesel and gasoline engines
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- developed for engines with diesel particulate filter (DPF)
- best motor cleanliness / reduced friction / long lifetime of the engine
- maximum fuel economy by dropped high temperature viscosity (HTHS)
- minimized wear by fast engine oiling
- maximum pollution prevention due to minimized oil related emissions

#### Specification / Recommendation

ACEA C1  
Jaguar/Land Rover STJLR.03.5005  
JASO DL-1  
Mazda DPF  
Mitsubishi DPF

### No. 10109

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-30 S

#### Description

- synthetic high performance / low friction motor oil
- for the latest generations of passenger cars and vans with diesel and gasoline engines
- high wear and corrosion protection
- excellent cleanliness of engine / long motor life
- fuel and oil economy

#### Specification / Recommendation

ACEA A5/B5  
API SL  
Jaguar/Land Rover STJLR.03.5003  
Ford WSS-M2C913-B/C/D  
Renault RN 0700

### No. 10060

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 20W-50

### Description

- high performance multigrade motor oil
- for gasoline and diesel engines of passenger cars
- lower fuel and oil consumption
- protection against black sludge
- keeps the engine clean
- modern oxidation inhibitors extend the service life of the oil
- optimal wear protection cares for long engine life

### Specification / Recommendation

ACEA A3/B4  
API SN/CF  
MB 229.1

## No. 10011

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 5W-30 DPF

### Description

- synthetic high performance motor oil
- especially for high power gasoline and diesel engines, newest models of passenger cars, sports cars and light commercial vehicles
- reduction of particle built-up / low ash
- compatible with the newest diesel particulate filters (DPF)
- very good low temperature properties
- low friction / excellent wear protection
- effective cleaning additives / extended oil drain intervals
- excellent motor protection and reduced of fuel consumption

### Specification / Recommendation

ACEA C3  
API SN/CF  
BMW Longlife-04  
MB 229.51  
VW 504 00/507 00

## No. 10125

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 5W-30 DPF-S

### Description

- synthetic high performance motor oil
- designed for high power gasoline and diesel engines
- reduction of particle built-up / low ash
- compatible with the newest diesel particulate filters (DPF)
- very good low temperature properties
- low friction / excellent wear protection
- effectively cleaning additives / extended oil drain intervals
- lowered fuel consumption

### Specification / Recommendation

ACEA C3  
API SN/CF  
BMW Longlife-04  
MB 229.51  
VW 504 00/507 00

## No. 10126

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 5W-30 C4

#### Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines with particulate filter (DPF)
- reduction of particle built-up
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- very good low temperature properties
- high wear and corrosion protection
- excellent cleanliness of engine / long motor life
- fuel and oil economy

#### Specification / Recommendation

ACEA C4-10  
MB 226.51/229.31/229.51  
Renault RN 0720 equipped with DPF

### No. 10121

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### Oilers SYNT SAE 5W-30 D

#### Description

- fully synthetic high performance motor oil
- for gasoline engines
- best wear protection / maximum motor cleanliness
- best low-temperature properties / cold start properties
- reduction of fuel and oil consumption

#### Specification / Recommendation

API SQ  
Daihatsu  
Fiat 9.55535-CR1  
Ford WSS-M2C929-A  
Ford WSS-M2C946-A  
Ford WSS-M2C946-B1  
Ford WSS-M2C961-A  
GM dexos1 Gen 3  
GM 6094M/4718M  
Honda/Acura HTO-06  
Hyundai  
ILSAC GF-7A  
Isuzu  
Kia  
Lexus  
Mazda  
Nissan  
Opel OV 040 1547 - G30  
Subaru  
Suzuki  
Toyota

### No. 10122

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 5W-40 MS

**No. 10149**

### Description

- fully synthetic high performance motor oil
- for gasoline and diesel particulate filter (DPF)
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- best wear protection / maximum motor cleanliness
- best low-temperature properties / cold start properties
- longer operating life of the engine by rapid oil circulation
- reduction of fuel and oil consumption

### Specification / Recommendation

ACEA C3  
 API SN/CF  
 API SN PLUS  
 BMW Longlife-04  
 Fiat 9.55535-S2  
 Ford WSS-M2C917-A  
 GM dexos2  
 MB 226.5  
 MB 229.31/229.51  
 Porsche A40  
 Renault RN 0700/0710  
 VW 502 00  
 VW 505 00/505 01 (PN)

### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

## OILERS SYNT SAE 5W-40

**No. 10068**

### Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- especially for fuel injected and turbo charged engines
- excellent cold start and fast oil feed even lower than -30°C
- optimized high temperature viscosity
- high wear and corrosion protection
- excellent cleanliness of engine / long motor life
- fuel and oil economy

### Specification / Recommendation

ACEA A3/B4  
 API SN/CF  
 BMW Longlife 98  
 Fiat 9.55535-M2  
 MB 229.3  
 Opel GM-LL-B-025  
 Porsche A40  
 PSA B71 2296  
 Renault RN 0710/0700  
 VW 502 00/505 00

### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

## OILERS SYNT SAE 5W-40 L

**No. 10168**

### Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- especially for fuel injected and turbo charged engines
- all seasons use in areas of strong daily or seasonal thermal fluctuations
- optimized high temperature viscosity
- high wear and corrosion protection
- excellent cleanliness of engine / long motor life
- fuel and oil economy

### Specification / Recommendation

ACEA A3/B4  
 API SP

### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

### OILERS SYNT SAE 5W-40 F

#### Description

- high performance synthetic motor oil
- designed for gasoline and diesel engines of passenger cars
- for fuel injected and turbo charged engines
- excellent cold start and fast oil feed even lower than -30°C
- reduced fuel consumption
- optimized high temperature viscosity / low friction properties
- high wear and corrosion protection
- longer motor life / excellent cleanliness of engine
- excellent performance persists even at long drain intervals

#### Specification / Recommendation

ACEA A3/B4  
API SP/CF  
BMW Longlife-01  
BMW Longlife-98  
Fiat 9.55535 M2  
Lamborghini  
Maserati  
MB 229.3/229.5  
MB 226.5  
Opel GM-LL-B-025  
Porsche A 40  
PSA B71 2296  
Renault RN 0700/0710  
VW 502 00/505 00

### No. 10001

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 5W-40 C3

#### Description

- fully synthetic high performance motor oil
- designed for gasoline and diesel engines with unit injector and vans
- low friction oil of the new generation
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- decreased particle build-up in diesel particulate filter (DPF)
- assist the environmental protection by lowering pollution
- best wear protection / maximum motor cleanliness
- reduction of fuel and oil consumption

#### Specification / Recommendation

ACEA C3  
ACEA A3/B4-04  
API SN/CF  
BMW Longlife-04  
Fiat 9.55535-S2  
Ford WSS-M2C917A  
Opel GM dexos2  
MB 229.31/229.51  
Porsche A40  
Renault RN 0700/0710  
VW 502 00/505 00/505 01 (PN)

### No. 10138

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 5W-50

### Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- especially for fuel injected and turbo charged engines
- excellent cold start and fast oil feed even lower than -30°C
- optimized high temperature viscosity
- high wear and corrosion protection
- excellent cleanliness of engine / longer motor life
- fuel and oil economy

### Specification / Recommendation

ACEA A3/B4  
API SN/CF  
BMW Longlife-98  
MB 229.3  
Opel GM-LL-B-025  
Porsche A40  
PSA B71 2296  
Renault RN 0710/0700  
VW 502 00/505 00

## No. 10101

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 20W-50 GT

### Description

- multigrade motor oil
- for gasoline and diesel engines
- protection against black sludge
- protection against thermal oxidation, corrosion and wear
- all seasons oil

### Specification / Recommendation

API SF/CD

## No. 10042

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 10W-40

### Description

- high performance synthetic motor oil
- designed for gasoline and diesel engines of passenger cars
- for fuel injected and turbo charged engines
- reduced fuel and oil consumption
- modern oxidation inhibitors / increased service life of the oil
- optimal wear protection cares for long engine life

### Specification / Recommendation

ACEA A3/B4  
API SN/CF  
PSA B71 2296  
Renault RN 0700  
MB 229.1  
VW 501 01/505 00

## No. 10058

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 10W-40 HC

#### Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- for turbo and non-turbo charged engines
- low evaporation loss
- very good cold start performance
- reduced consumption of fuel and oil
- excellent oxidative stability / keeps engine clean
- optimal wear protection cares for long engine life

#### Specification / Recommendation

ACEA A3/B4  
API SP  
Fiat 9.55535-G2/D2  
MB 229.1/229.3  
PSA B71 2296  
Renault RN 0700  
VW 501 01/505 00

### No. 10093

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS RACING SYNT SAE 10W-60

#### Description

- fully synthetic racing performance motor oil
- for turbo charged and fuel injected engines
- special additive components
- excellent cold-starting properties
- optimal piston cleanliness
- maximum wear protection

#### Specification / Recommendation

ACEA A3/B4  
API SP/CF

### No. 10070

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SAE 20W-50 X

#### Description

- super high performance diesel (SHPD) motor oil
- multifunctional for diesel and gasoline engines also with turbocharger
- made for passenger cars, trucks, busses, farm and off road equipment
- meets specifications of European, American and Japanese manufacturers
- excellent thermal / oxidative stability
- reduces sludge and deposit built-up
- maximum oil drain intervals due to highest TBN reserves
- best seal and elastomer compatibility
- slow oil ageing even at high temperatures
- all season oil for mixed fleets

#### Specification / Recommendation

ACEA E7-10  
ACEA A3-/B4-10  
API CI-4/SL  
Allison C-4  
CAT ECF-1-a/ECF-2  
Cummins CES 20071/-75/-76/-77/-78  
DEUTZ DQC III-10  
Fiat 9.55535-G2/D2  
GLOBAL DHD-1  
JASO DH-1  
Mack EO-M PLUS  
MAN M 3275  
MB 228.3/229.1  
MTU Type 2  
Renault RLD-2  
Volvo VDS-3

### No. 10130

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 40 CI-4

### Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

### Specification / Recommendation

API CI-4/SL

## No. 10110

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 50 CI-4

### Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

### Specification / Recommendation

API CI-4/SL

## No. 10115

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 60 CI-4

### Description

- mono grade motor oil
- mineral base oils and selected additives
- for normal aspired engines and also suitable for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- good detergency and dispersancy
- provides motor cleanliness
- corrosion and wear protection as well as
- oxidation protection

### Specification / Recommendation

API SF/CF

## No. 10016

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-20

#### Description

- fully synthetic motor oil
- high performance lubricant
- for the most gasoline engines of passenger cars
- excellent lubricity
- stable lubrication film at all operation conditions
- very good cold starting properties even at low temperatures
- long motor life / complex wear protection / cleanliness
- low oil consumption / high fuel efficiency

#### Specification / Recommendation

API SQ  
Chrysler MS-6395  
Daihatsu  
Ford WSS-M2C947-A  
Ford WSS-M2C947-B1  
Ford WSS-M2C962-A  
GM dexos1 Gen 3  
Honda  
Hyundai  
ILSAC GF-7A  
Isuzu  
Kia  
Lexus  
Mazda  
Nissan  
Subaru  
Suzuki  
Toyota

### No. 10134

#### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-20 F

#### Description

- fully synthetic low friction motor oil
- maximum thermal and mechanical stability
- excellent viscosity temperature / low evaporation loss
- very good cold starting properties even at low temperatures
- reduces fuel consumption
- highly effective dispersant additives

#### Specification / Recommendation

ACEA C5/C6  
API SP/SP RC  
Ford WSS-M2C956-A1  
ILSAC GF-6A  
Porsche C20  
VW 508 00/509 00  
VW TL 52577

### No. 10135

#### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 0W-20 FE

#### Description

- fully synthetic low friction motor oil
- for modern fuel economy passenger cars and light vans
- superb thermal and mechanical stability
- excellent viscosity-temperature profile
- very good cold starting properties even at low temperatures
- reduces fuel consumption
- highly effective dispersant additives

#### Specification / Recommendation

ACEA C5  
API SP (RC)  
BMW LL17FE+/BMW LL14FE+  
Chrysler MS-12145  
Fiat 9.55535-GSX  
Ford WSS-M2C947-B1  
Ford WSS-M2C962-A1  
ILSAC GF-6A  
JLR STJLR 03-5006-16  
MB 229.71  
MB 229.72  
Opel OV0401547

### No. 10136

#### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 10W-30

**No. 10184**

### Description

- synthetic low friction motor oil
- for all passenger cars with gasoline and diesel engines
- reduced oil and fuel consumption
- excellent dispersancy / keeps motor clean
- very good low-temperature properties / smooth cold start
- modern oxidation inhibitors
- increased service life of the oil

### Specification / Recommendation

ACEA A3/B4  
API SP/CF  
MB 229.1  
VW 505 00  
Daihatsu  
Honda  
Hyundai  
Kia  
Lexus  
Mazda  
Mitsubishi  
Nissan  
Subaru  
Suzuki  
Toyota

### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 10W-30 CK-4

**No. 10143**

### Description

- synthetic high-performance motor oil
- latest generation of low-emission engines
- low SAPS technology
- high shear stability followed by a stable lubrication film under extreme conditions at higher temperatures
- provides excellent fuel economy
- very good oxidation stability

### Specification / Recommendation

ACEA E7/E11  
API CK-4/CJ-4/SN  
API CI-4/CI-4 Plus  
CAT ECF-3  
Cummins CES 20086  
DAF PSQL 2.1E  
Detroit Diesel DFS93K222  
Detroit Diesel DDC93K222  
Deutz DQC-III-10LA/18LA  
Ford WSS-M2C171-F1  
Jaso DH-2  
Mack EOS-4.5  
MAN M 3575/M 3775/M 3275  
MB 228.31  
MTU Type 2.1  
Renault VI RLD-3  
Volvo VDS-4.5

### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 10W-40 CK-4

**No. 10144**

#### Description

- synthetic high-performance motor oil
- latest generation of low-emission engines
- low SAPS technology
- high shear stability followed by a stable lubrication film under extreme conditions at higher temperatures
- provides excellent fuel economy
- very good oxidation stability

#### Specification / Recommendation

ACEA E7/E11  
API CK-4/CJ-4/SN  
API CI-4/CI-4 Plus  
CAT ECF-3  
Cummins CES 20086  
Detroit Diesel DFS93K222  
Detroit Diesel DDC93K222  
Deutz DQC-III-10LA/18LA  
Ford WSS-M2C171-F1  
Jaso DH-2  
John Deere JDQ-78X  
Mack EOS-4.5  
MAN M 3575/M 3775/M 3275  
MB 228.31  
MTU Type 2.1  
Renault VI RLD-3  
Volvo VDS-4.5

#### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 10W-40 HC

**No. 10004**

#### Description

- synthetic ultra-high performance diesel motor oil (UHPD)
- for EURO 4 and EURO 5 commercial engines (2014 regulation by law)
- high wear protection / reduces friction
- very good cold start performance
- very high oxidation resistance
- protects against corrosion and black sludge
- reduces oil consumption
- excellent viscosity / temperature behavior
- high shear stability
- low evaporation tendency
- most extended oil drain intervals
- great fuel economy characteristics

#### Specification / Recommendation

ACEA E4/E7  
API CI-4 + UHPD  
CAT ECF-1-a/ECF 2  
Cummins CES 20076/20077/20078  
Deutz DQC IV-10  
Global DHD-1  
IVECO (if recommended for ACEA E4/E7)  
MACK EO-M+  
MAN M 3277/M 3377  
MB 228.5  
MTU Type 3  
Renault RXD/VI RLD-2  
Scania LDF-3  
Volvo VDS-3

#### Packaging Units

5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SYNT SAE 10W-40 LA

**No. 10028**

### Description

- synthetic ultra-high performance diesel motor oil (UHPD)
- for EURO 5 and EURO 6 commercial engines (2014 regulation by law)
- low sulphated ash sulphur and phosphorus content (low SAPS)
- for the trouble-free operating (particulate filter)
- high wear protection / reduces friction
- low evaporation tendency / good elastomer compatibility
- very high oxidation resistance
- protects against corrosion and black sludge
- reduces oil consumption
- excellent viscosity / temperature behavior
- high shear stability
- great fuel economy characteristics

### Specification / Recommendation

ACEA E7/E8/E11  
 API CK-4  
 CAT ECF-3  
 Cummins CES 20086  
 DAF  
 DDC 93K222  
 Deutz DQC IV-18 LA  
 Jaso DH-2  
 John Deere JDQ-78X  
 Mack EO-S 4.5  
 MAN M 3477, M 3775, M 3575  
 MB 226.9/228.31/MB 228.51  
 MTU Typ 3.1  
 Renault VI RLD-3  
 Renault Truck RXD/RGD  
 Scania LA  
 Volvo CNG/VDS 4.5

### Packaging Units

5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

## OILERS SYNT SAE 10W-40 X

**No. 10003**

### Description

- synthetic high performance / low friction oil
- for modern generations of diesel and gasoline motors
- excellent viscosity / temperature behavior
- high shear stability / support all season use
- stable lubrication film under extreme conditions / high temperature
- very low oil consumption
- very good oxidation stability

### Specification / Recommendation

ACEA E7  
 API CI-4/CF/SL  
 Caterpillar ECF-1a/ECF-2  
 Cummins CES 20077  
 Cummins CES 20078  
 Deutz DQC III-18  
 DDC 93K215  
 Global DHD-1  
 Jaso DH-1  
 Mack EO-M Plus/EO-N  
 MAN M 3275  
 MB 228.3  
 MTU Type 2  
 Renault RLD/RLD2  
 Volvo VDS-3

### Packaging Units

5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

### OILERS AGRA SAE 10W-30

**No. 13027**

#### Description

- multigrade Super-Tractor-Oil-Universal (STOU)
- universal, all season oil for all types of agricultural machines
- for engines, gears, hydraulics and brake systems (wet brakes)
- excellent operation for engines, gears, axes, differentials, hydraulic and brake systems
- very good protection against corrosion / black sludge
- high wear protection at full engine load
- low foaming tendency

#### Specification / Recommendation

ACEA E3  
API CF/CG-4/SF  
API GL-4  
Allison C-4  
Case NH MAT 3525/3526  
Caterpillar TO-2  
Ford M2C159B/C  
HVLDP-D 68 accord. DIN 51 524 part 3\*  
John Deere JDM 27  
Massey Ferguson M 1139/1144/1145  
MB 227.1/228.1  
ZF TE-ML-06A/-06B/-06C/-07B  
\*excepted demulsibility (on TDS only)

#### Packaging Units

20 l pail  
60 l drum  
200 l drum

### OILERS AGRA SAE 10W-40

**No. 13055**

#### Description

- synthetic Super-Tractor-Oil-Universal (STOU)
- universal, all season oil for all types of agricultural machines
- for engines, gears, hydraulics and brake systems (wet brakes)
- excellent operation for engines, gears, axes, differentials, hydraulic and brake systems
- very good protection against corrosion / black sludge
- high wear protection at full engine load
- low foaming tendency

#### Specification / Recommendation

ACEA E3  
API CG-4  
API GL-4  
HVLDP-D accord. DIN 51 524 part 3 (for 10W40)  
Allison C-4  
Case M5 /1118/1207/1209/  
MAT3525/CS/CVX  
Claas Renault Agriculture  
Harvester B6  
Fendt Vario  
Ford M2C 159B/C, M2C 86B/C,  
M2C 134D  
John Deere JDM/J20C/J27  
Landini / Lindner / Mc-Cormick  
Massey Ferguson M1135 to 1145  
New Holland NH 410B / 420A /  
526C  
Same-Deutz-Lamborghini-  
Hirlimann T3245/3340/3345/  
3445/3450/3550  
Valmet  
ZF TE-ML-06B (inc.06R),-06C,-  
07B  
Steyr Serie 900/9000/CVT

#### Packaging Units

20 l pail  
60 l drum  
200 l drum

# MULTIFUNCTIONAL OILS

## OILERS AGRA SAE 15W-30

**No. 13014**

### Description

- Super High Performance Diesel (SHPD) motor oil
- multi functional for diesel and gasoline engines also turbochargers
- made for passenger, trucks, busses, farm and off road equipment
- meets specifications of European, American and Japanese manufacturers
- excellent thermal / oxidative stability
- reduces sludge built-up und deposits
- maximum oil drain intervals by highest TBN reserve
- best seal and elastomer compatibility
- reduces oil ageing even at high temperatures
- all season oil for mixed fleet

### Specification / Recommendation

API CF/CG-4/SF  
API GL-4  
ACEA E3-96  
Allison C-4  
Case NH MAT 3525/3526  
Caterpillar TO-2  
Ford M2C159B/C  
HVLP-D 68 accord. DIN 51 524 part 3 (for 15W30)  
HVLP-D 100 accord. DIN 51 524 part 3 (for 15W40)  
John Deere JDM 27  
Massey Ferguson M 1139/1144/1145  
MB 227.1/228.1  
ZF TE-ML-06A/-06B/-06C/-07B

### Packaging Units

20 l pail  
60 l drum  
200 l drum

## OILERS UTTO SAE 10W-30

**No. 13013**

### Description

- Universal Tractor Transmission Oil (UTTO)
- for gears, hydraulics and wet breaks
- very good anti wear and anti corrosion properties
- excellent oxidation stability
- extended oil drain intervals
- high shear stability

### Specification / Recommendation

API GL-4  
Allison C-4/C-3  
Case MS-1204, -1205, -1206, -1207, -1209, -1210  
Caterpillar TO-2  
Deutz Hydr Trans Fluid  
Ford M2C 134D, M2C 86A-C  
John Deere J-20C/D  
Massey Ferguson M 1143, 1145  
ZF TE-ML-03E/-06

### Packaging Units

20 l pail  
60 l drum  
200 l drum

## OILERS UTTO SAE 10W-30

**No. 13017**

### Description

- high performance transmission fluid
- excellent corrosion protection for steel and non-ferrous metals
- good cold flow properties
- low friction
- high elastomer compatibility

### Specification / Recommendation

### Packaging Units

20 l pail  
60 l drum  
200 l drum

### OILERS SAE 50 TO-4

#### Description

- high performance transmission fluid
- excellent corrosion protection for steel and non-ferrous metals
- good cold flow properties
- low friction
- high elastomer compatibility

#### Specification / Recommendation

API GL-4  
API CF  
Caterpillar TO-4  
Komatsu

### No. 13023

#### Packaging Units

20 l pail  
60 l drum  
200 l drum

# MONO-GRADE MOTOR OILS

## OILERS SAE 10 HD

### Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

### Specification / Recommendation

API SF/CF/CF-4

## No. 10015

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 30 HD

### Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

### Specification / Recommendation

API SF/CF/CF-4

## No. 10022

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 40 HD

### Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

### Specification / Recommendation

API SF/CF/CF-4

## No. 10012

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SAE 50 HD

#### Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN / improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

#### Specification / Recommendation

API SF/CF/CF-4

### No. 10040

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SYNT SAE 5W-20

#### Description

- fully synthetic high performance motor oil
- especially designed for gasoline / diesel passenger cars and light vans
- low viscosity / fuel saving
- stable lubrication film even at low temperatures
- long motor life due to complex wear protection/cleanliness
- low oil consumption / high fuel efficiency / reduced exhaust gas emissions
- long oil drain intervals

#### Specification / Recommendation

API SQ  
Chrysler MS-6395  
Daihatsu  
Ford WSS-M2C945-A  
Ford WSS-M2C945-B1  
Ford WSS-M2C930-A  
Ford WSS-M2C960-A  
GM dexos1 Gen 3  
GM 6094-M  
Honda  
Hyundai  
ILSAC GF-7A  
Isuzu  
Kia  
Lexus  
Mazda  
Nissan  
Subaru  
Suzuki  
Toyota

### No. 10186

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SAE 20W-50 X

#### Description

- fully synthetic low friction motor oil
- for all passenger car gasoline and diesel engines
- reduced oil and fuel consumption
- excellent dispersancy
- keeps motor clean
- very good low-temperature properties / smooth cold start
- modern oxidation inhibitors
- increased service life of the oil

#### Specification / Recommendation

ACEA A3/B4  
API SP/CF

### No. 10185

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# MONO-GRADE MOTOR OILS

## OILERS SYNT SAE 5W-30 LS

### Description

- high performance synthetic motor oil
- for EURO 5 and EURO 6 class commercial engines
- under limits for sulphated ash, sulphur and phosphorus content (low SAPS)
- for trouble-free operating (particle filter)
- high wear protection / reduces friction
- low evaporation tendency / good elastomer compatibility
- very high oxidation resistance
- protects against corrosion and black sludge
- reduce oil consumption
- excellent viscosity / temperature behaviour
- high shear stability
- great fuel economy characteristics

### Specification / Recommendation

ACEA E7/E8/E11/E4  
API CJ-4  
CAT ECF-3  
Cummins CES 20081  
DAF  
Detroit Diesel DDC 93K218  
Deutz DQC IV-10 LA  
Iveco  
JASO DH 2  
Mack EO-O Premium Plus  
Mack EO-N Premium Plus  
Mack EO-M Plus  
MAN M 3677/M 3477/M 3691  
MAN M 3271-1/M 3575  
MB 228.51/228.31/235.28  
MTU Type 3.1 and 2.1  
Renault Truck RLD-3  
Scania LA und LDF 4  
Voith Retarder Class B  
Volvo VDS-4

## No. 10046

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 10 GST

### Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

### Specification / Recommendation

API SF/CD  
DIN 51 506

## No. 10021

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS SAE 30 GST

### Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

### Specification / Recommendation

API SF/CD  
DIN 51 506

## No. 10052

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SAE 40 GST

#### Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

#### Specification / Recommendation

API SF/CD  
DIN 51 506 (not to use in compressors where the manufacturer requires zinc free product)

### No. 10047

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SAE 50 GST

#### Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

#### Specification / Recommendation

API SF/CD  
DIN 51 506 (not to use in compressors where the manufacturer requires zinc free product)

### No. 10091

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS SAE 20W-20 GST

#### Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

#### Specification / Recommendation

ACEA A3/B4  
API SP/CF

### No. 10023

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS 2T-F

### Description

- fully synthetic high performance oil
- suitable for air and water cooled racing engines
- meets most specification requirements of all two-stroke motor manufacturers
- latest additive technology / low ash
- optimal motor lubrication even under high-speed racing conditions
- improved pollution control by scentless and smokeless combustion

### Specification / Recommendation

API TC  
ISO-L-EGD  
JASO FD

## No. 10032

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS 2T-S

### Description

- synthetic high performance two-stroke oil
- can be used universally in two-stroke engines
- pressure resistant oil film at all lubrication points
- excellent anti corrosion, anti oxidation and anti wear behavior
- excellent high temperature performance / no smoke

### Specification / Recommendation

API TC  
ISO-L-EGD  
JASO FD

## No. 10030

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS 2T-M

### Description

- two-stroke motor oil for mixture and separate lubrication
- based on mineral oil and applicable for two-stroke
- protects the engine against corrosion and wear
- is self-mixing and forms a homogeneous mixture with the fuel

### Specification / Recommendation

API TC  
ISO-L-EGC  
JASO FC

## No. 10031

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS 4T-S 10W-40

**No. 10049**

#### Description

- high performance multigrade oil for motorcycles
- especially for motorcycles with air and water cooled four-stroke engines of highest output
- ideal partner for all sportive motorcycles
- optimal lubrication in motor and in gear
- excellent motor cleanliness especially at pistons and valves

#### Specification / Recommendation

ACEA A3-04  
API SN Plus  
JASO MA2

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS 4T-M 20W-50

**No. 10050**

#### Description

- high performance multigrade oil for motorcycles
- especially for motorcycles with air and water cooled four stroke engines of highest output
- ideal partner for all sportive motorcyles
- optimal lubrication in motor and in gear
- excellent motor cleanliness especially at pistons and valves

#### Specification / Recommendation

ACEA A3-04  
API SN  
JASO MA2

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# AUTOMATIC TRANSMISSION FLUIDS (ATF)

## OILERS ATF 4-0 R

### Description

- automatic transmission fluid
- usable in passenger and commercial cars, other vehicles and aggregates
- for power steering systems, automatic and manual transmissions power shift gear, hydraulic systems
- very good friction stability
- excellent low and high temperature shifting performance
- good anti-wear properties / maximum lifetime
- very good ageing and oxidation stability
- reduced foaming tendency
- prevents from corrosion, wear and deposits
- good sealing compatibility

### Specification / Recommendation

GM DEXRON IID  
GM DEXRON III  
Allison C3/C4  
Caterpillar TO-2  
Ford SQM-9010B  
Ford M2C-38CJ, 166H, 185A  
MAN 339 Typ D  
MB 236.7  
Voith  
ZF TE-ML 03D, 04D, 09A, 11A, 14A

## No. 15011

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS ATF 4-0 F

### Description

- automatic transmission fluid
- usable in passenger and commercial cars, other vehicles and aggregates
- for power steering systems, automatic and manual transmissions power shift gear, hydraulic systems
- very good friction stability
- excellent low and high temperature shifting performance
- good anti-wear properties / maximum lifetime
- very good ageing and oxidation stability
- reduced foaming tendency
- prevents from corrosion, wear and deposits
- good sealing compatibility

### Specification / Recommendation

GM DEXRON IID  
GM DEXRON III  
Allison C3/C4  
Caterpillar TO-2  
Ford SQM-9010B  
Ford M2C-38CJ, 166H, 185A  
MAN 339 Typ D  
MB 236.7  
Voith  
ZF TE-ML 03D, 04D, 09A, 11A, 14A

## No. 15021

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS ATF 9-0 R

#### Description

- synthetic automatic transmission fluid
- automatic transmission fluid for passenger cars and heavy duty vehicles
- meets the requirements of most current specifications of American, European and Asian manufacturers
- prevents from miss disposition
- smart ware housing
- excellent low-temperature shifting performance
- long-term friction stability
- best anti-wear properties / maximum lifetime
- outstanding ageing and oxidation stability
- reduced foaming tendency
- prevents reliably from corrosion, wear and deposits
- good sealing compatibility

#### Specification / Recommendation

DEXRON IIIH / DEXRON IIIG  
DEXRON IIE / DEXRON IID  
Allison C-4  
Allison TES, 389  
CAT TO-2  
Ford Mercon  
Ford M2C138-CJ, M2C 166-H  
MB 236.1/236.5/236.6/236.7/236.9  
MAN 339 Typ Z1/V1, Z2/V2  
TASA  
Volvo 97340, 97341  
Voith 55.6335 / 55.6336  
ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 17C

### No. 15020

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS ATF 9-0 F

#### Description

- ynthetic automatic transmission fluid
- automatic transmission fluid for passenger cars and heavy duty vehicles
- meets the requirements of most current specifications of American, European and Asian manufacturers
- prevents from miss disposition
- smart ware housing
- excellent low-temperature shifting performance
- long-term friction stability
- best anti-wear properties / maximum lifetime
- outstanding ageing and oxidation stability
- reduced foaming tendency
- prevents reliably from corrosion, wear and deposits
- good sealing compatibility

#### Specification / Recommendation

DEXRON IIIH / DEXRON IIIG  
DEXRON IIE / DEXRON IID  
Allison C-4  
Allison TES, 389  
CAT TO-2  
Ford Mercon  
Ford M2C138-CJ, M2C 166-H  
MB 236.1/236.5/236.6/236.7/236.9  
MAN 339 Typ Z1/V1, Z2/V2  
TASA  
Volvo 97340, 97341  
Voith 55.6335 / 55.6336  
ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 17C

### No. 15026

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# AUTOMATIC TRANSMISSION FLUIDS (ATF)

## OILERS ATF 9-1 R

**No. 15081**

### Description

- synthetic automatic transmission fluid
- meets major Asian (Japanese & Korean) OEM specifications
- smooth gear shift
- fuel economical
- excellent anti-corrosion and anti-wear properties for gearboxes

### Specification / Recommendation

GM DEXRON  
Allison  
BMW/Mini  
Bosch  
Daihatsu  
Daimler Mercedes  
Fiat Chrysler  
Ford/Lincoln/Mercury  
GM/GMC/Opel/Saturn  
Honda/Acura  
Hyundai/Kia  
Idemitsu  
Isuzu  
Jaso  
Jaguar  
Land Rover  
MAN  
Mazda  
Mercon  
Mitsubishi  
Mobil  
Nissan/Infinity  
Porsche  
Peugeot  
PSA  
Renault  
Rolls Royce  
Saab  
Shell  
Subaru  
Suzuki  
Toyota/Lexus/Scion  
VW/Audi  
Voith  
Volvo  
ZF

for more specs please see TDS

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## AUTOMATIC TRANSMISSION FLUIDS (ATF)

### OILERS ATF 9-1 R

No. 15091

#### Description

- synthetic automatic transmission fluid
- meets major Asian (Japanese & Korean) OEM specifications
- smooth gear shift
- fuel economical
- excellent anti-corrosion and anti-wear properties for gearboxes

#### Specification / Recommendation

GM DEXRON  
Allison  
BMW/Mini  
Bosch  
Daihatsu  
Daimler Mercedes  
Fiat Chrysler  
Ford/Lincoln/Mercury  
GM/GMC/Opel/Saturn  
Honda/Acura  
Hyundai/Kia  
Idemitsu  
Isuzu  
Jaso  
Jaguar  
Land Rover  
MAN  
Mazda  
Mercon  
Mitsubishi  
Mobil  
Nissan/Infinity  
Porsche  
Peugeot  
PSA  
Renault  
Rolls Royce  
Saab  
Shell  
Subaru  
Suzuki  
Toyota/Lexus/Scion  
VW/Audi  
Voith  
Volvo  
ZF

for more specs please see TDS

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# AUTOMATIC TRANSMISSION FLUIDS (ATF)

## OILERS ATF 9-1 R

### Description

- synthetic lifetime automatic transmissions fluid
- especially made for Mercedes Benz
- extremely shear stable VI-improver
- modern anti-wear additives and balanced friction modifiers
- excellent gear changing properties

### Specification / Recommendation

MB 236.12  
MB 236.14  
Audi/VW G 052 162 (A1, A2)  
Jaguar JLM 20238  
Porsche P/N 999 917 547 00  
PSA Peugeot/Citroen P/N Z  
000169756

## No. 15050

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS ATF 9-4 F

### Description

- synthetic lifetime automatic transmission fluid
- particularly made for Mercedes Benz
- extremely shear stable VI-improver
- modern anti-wear additives and balanced friction modifiers
- smooth gear shifting properties

### Specification / Recommendation

MB 236.12  
MB 236.14  
Audi/VW G 052 162 (A1, A2)  
Jaguar JLM 20238  
Porsche P/N 999 917 547 00  
PSA Peugeot/Citroen P/N Z  
000169756

## No. 15051

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS ATF 9-5 B

### Description

- synthetic automatic transmission fluid especially developed for Mercedes-Benz-7-speed automatic transmission
- extremely shear stable with modern anti-wear additives
- reduced viscosity for maximum fuel efficiency
- adapted friction coefficient behaviour for smooth shifting operations
- best wear protection properties for reliable operation and the longest service life
- outstanding oxidation and thermal stability
- neutral to metals and sealing materials

### Specification / Recommendation

MB 236.15

## No. 15060

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS ATF 9-6 LV F

No. 15037

#### Description

- synthetic automatic transmission fluid
- optimized for passenger car applications
- for an extensive range of European and Asian passenger cars
- can be used in commercial vehicle applications and power steering
- exceptional oxidation behaviour
- anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency
- good sludge and varnish control

#### Specification / Recommendation

DEXRON VI  
Aisin Warner  
Bentley  
BMW/Mini  
Chrysler/Dodge/Jeep  
Daimler/Mercedes  
Fiat  
Ford/Lincoln/Mercury  
GM/GMC/Opel/Saturn  
Honda  
Hyundai/Kia  
Isuzu  
Jaguar  
JASO  
Jeep  
Land Rover  
Maserati  
Mazda  
Mercon  
Mitsubishi  
Nissan  
Porsche  
Saab  
Shell  
Subaru  
Suzuki  
Toyota/Lexus  
Volvo  
VW/Audi  
ZF

for more specs please see TDS

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# AUTOMATIC TRANSMISSION FLUIDS (ATF)

## OILERS ATF 9-6 LV R

**No. 15047**

### Description

- synthetic automatic transmission fluid
- optimized for passenger car applications
- for an extensive range of European and Asian passenger cars
- can be used in commercial vehicle applications and power steering
- exceptional oxidation behaviour
- anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency
- good sludge and varnish control

### Specification / Recommendation

DEXRON VI  
Aisin Warner  
Bentley  
BMW/Mini  
Chrysler/Dodge/Jeep  
Daimler/Mercedes  
Fiat  
Ford/Lincoln/Mercury  
GM/GMC/Opel/Saturn  
Honda  
Hyundai/Kia  
Isuzu  
Jaguar  
JASO  
Jeep  
Land Rover  
Maserati  
Mazda  
Mercon  
Mitsubishi  
Nissan  
Porsche  
Saab  
Shell  
Subaru  
Suzuki  
Toyota/Lexus  
Volvo  
VW/Audi  
ZF

for more specs please see TDS

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS ATF 9-8

#### Description

- synthetic automatic transmission fluid especially developed for modern ZF 6-, 8- and 9- speed
- highest quality features
- high load capacity and extremely wear reducing
- excellent low- temperature switching behavior
- minimal evaporation losses
- adapted friction characteristics for sport gear changes
- no effect on sealing materials
- good ageing, oxidation and thermal stability
- excellent protection against foaming

#### Specification / Recommendation

BMW L12108 (83 22 2 152 426)  
BMW 83 22 2 305 397  
BMW 83 22 2 289 720 (ATF3+)  
Chrysler 68157995AA  
FIAT 9.55550-AV5  
Honda Type 3.1  
Jaguar 02JDE 26444  
Jeep ATF LGF8  
Land Rover LR 023288/232289  
MB 236.82  
Mopar 68157995AA  
VW/Audi G 060 162 A1/A2/A6, G  
055 162 (A2, A6)  
VW G 055 540 (A2)  
ZF Lifeguardfluid 8 (S671 090 312)  
ZF Lifeguardfluid 9 (AA01.500.001)  
ZF Lifeguard 6 (S671 090 255)

### No. 15063

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS ATF 9-9 F

#### Description

- synthetic automatic transmission fluid especially developed for Mercedes-Benz-9- automatic transmission (9G-Tronic)
- extremely shear stable with modern anti-wear additives
- high load capacity and extremely wear reducing
- excellent low- temperature switching behavior
- minimal evaporation losses
- no effect on sealing materials
- good ageing, oxidation and thermal stability
- excellent protection against foaming

#### Specification / Recommendation

MB 236.16/236.17  
MB 236.41  
Aisin AW F8FXX  
DSIH 6p805 (Geely, Ssangyong,  
Mahindra 6sp)  
Hyundai NWS-9638  
Hyundai/Kia SP-IV, SPH-IV, SP-IV  
RR  
JASO 1-A-LV  
Mitsubishi ATF-J3, ATF-PA  
Mopar 68218925AA  
Nissan Matic S, Matic W  
Saab 93 165 147  
Volvo 6 speed MY 2011-2013 (P/N  
31256774 or 31256675)  
VW G 052 540, G 055 005,  
G 055 162  
ZF TE-ML 13  
ZF 6 Speed (S671 090 255)

### No. 15017

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# AUTOMATIC TRANSMISSION FLUIDS (ATF)

## OILERS ATF 10 F

**No. 15100**

### Description

- synthetic automatic transmission fluid especially developed for 6, 8- and 10-automatic transmission (6-8-10G-Tronic)
- ultra low viscosity for high fuel economy
- extremely shear stable with modern anti-wear additives
- high load capacity and extremely wear reducing
- excellent low- temperature switching behavior
- minimal evaporation losses
- no effect on sealing materials
- good ageing, oxidation and thermal stability
- excellent protection against foaming

### Specification / Recommendation

Aisin Warner AW-2  
BMW 83 22 2 413 477 (ATF 7)  
Ford WSS-M2C949-A  
Ford Mercon ULV  
Ford P/N XT-12-ULV [ULV]  
Ford Motorcraft XT-12-QULV  
GM Dexron ULV  
GM 19352619  
Mazda ATF A7  
MB 236.16  
MB 236.17  
Nissan Matic P, P/N 999MP-  
MTP10P  
PSA 16 350 560 80  
Volvo P/N 31 492 172, 31 492 173  
VW G 053 001 A2  
VW G 060 540 A2

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS ATF CVT

**No. 15055**

#### Description

- synthetic automatic transmission fluid
- especially designed for the use in modern (CVT= Continuous Variable Transmission) transmissions
- fulfills the unique requirements of belt and chain CVT's
- excellent metal / metal friction behaviour
- optimal low-temperature properties
- most stable friction behaviour during whole operation life
- reliable power transmission / low friction losses are always granted
- outstanding wear protection under high loads
- good ageing and oxidation stability
- excellent protection against foaming

#### Specification / Recommendation

BMW 8322 0 429 154  
 BMW 8322 0 429 159  
 Chrysler/Dodge/Jeep NS-2  
 Chrysler/Dodge/Jeep/Mopar CVT+4  
 Daihatsu Ammix CVT DC/DFC/DFE  
 Daihatsu TC  
 ELFMATIC CVT  
 Ford CVT 23, 30  
 Ford WSS-M2C928-A  
 Ford WSS-M2C933-A  
 GM/Saturn DEX-CVT  
 Honda ATF-Z1\*, HCF2  
 Honda HMMF\*  
 Hyundai/Kia SP-III (CVT model)  
 Hyundai/Kia CVT-J1  
 Hyundai CVTF  
 JASO M358  
 Mazda JWS 3320  
 MB 236.20  
 MB A 001 989 46 03  
 Mini Cooper EZL799/EZL799A/ZF  
 CVT V1  
 Mercon C  
 Mitsubishi CVTF-J1 (MMC  
 Diaqueen CVT Fluid J1)  
 Mitsubishi (Diaqueen) SP-III (CVT  
 model only)  
 Mitsubishi CVTF-J4 & J4+ (MMC  
 Diaqueen CVT Fluid J4 & J4+)  
 Nissan NS-1, NS-2, NS-3  
 Punch CVT  
 Subaru ECVT, iCVT, iCVT FG / NS-2  
 Subaru Lineartronic ECVT  
 Subaru Lineartronic iCVT  
 Subaru Lineartronic High Torque  
 (HT) CVTF, Subaru Lineartronic  
 chain CVTF/CVTF II  
 Suzuki CVTF TC, CVT Green 1/2/1V,  
 NS-2, CVTF 3320  
 Toyota CVTF TC, CVTF FE  
 VW/Audi TL521 16 (G 052 516 A2)  
 VW/Audi TL521 80 (G 052 180 A1/  
 A2/A6)  
 \*use in Honda with starting clutch is  
 not recommended

#### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

# AUTOMATIC TRANSMISSION FLUIDS (ATF)

## OILERS ATF DSG F

No. 15035

### Description

- synthetic ATF for double clutch transmission (DCT)
- developed for the latest generation of DCT
- extremely high wear resistance
- high thermal stability
- excellent viscosity
- good temperature behaviour
- low pour point
- foamless even under difficult conditions
- high oxidation stability
- carrying capacity
- optimum friction characteristics
- neutral to metals and sealing materials

### Specification / Recommendation

Audi/Volkswagen/Seat/Skoda - G 052 182 A2/A6 (TL 52 182), G 052 529 A2/A6 (TL 52 529), G 055 529 (TL 52 529-C)  
BMW -DCTF-1 (83 220 440 214), DCTF-1+, DCTF-2  
BMW 6-Speed DCT, MTF-LT-5 (83 22 2167 666), 83 22 2 147 477, 83 22 2 148 578, 83 22 2 148 579, 83 22 2 446 673 Citroen/Peugeot-6DCT451 (PSA 9734.S2)  
Ford WSS-M2C200-D2/ XT-11-QDC/ WSS-M2C-936-A, part # 1490763/1490761/ WSS-M2C218-1A, -F-DC, part # KU7J M2C218AA  
Ford/Nissan Powershift 6-Speed (GFT)  
Mercedes Benz - MB 236.5/236.21/ 236.22/236.24/239.21  
Mitsubishi - TC-SST 6-Speed (GFT), MZ320065 DiaQueen SSTF-1; DCT Transmission oil for ZF  
Porsche - 043 207 29, 043 207 30, 000 043 20, 000 043 305 13, 999 917 080 01, 000 043 210 44, 971 094 307 02A  
Renault 77 11 785 243 (DW5) / EDC 6-Speed (Getrag), EDC 7 /- BOT 450  
Volvo Powershift 6-Speed (GFT)/1161838/1161839  
VW G 052 536, 055 536; VW Audi G 052 512; VW (Audi, Seat, Skoda) 6-Speed; Audi TL 52529/G 052 529 A2/A6 (fluid) / DSG 7= S-tronic 7/ 7-Speed VW (Audi, Seat, Skoda); VW/Audi G 055 529 A1/A2/A6  
ZF TE-ML 11 (ZF004743), ZF Lifeguard Fluid 8.2  
for more specs please see TDS

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS GEAR OIL SAE 75W SYNT

No. 15009

#### Description

- high performance low friction gear oil
- for lubrication of synchronized and nonsynchronized
- standard transmissions
- excellent high pressure- and wear protection properties
- very good properties in corrosion- and rust protection
- low foaming tendency and excellent aging stability
- high viscosity index and low pour point care for easy gear changing even at lot temperatures
- reduced oil consumption and extended oil drain intervals
- specially recommended for commercial vehicles with BMW, VW and Mercedes Benz manual transmissions

#### Specification / Recommendation

API GL-4  
BMW MTF LT-2/-3/-4  
FORD WSS-M2C200-D2  
Fiat MZ 7  
GM 1940764/W16612  
MB 235.10  
PSA B71 2316 (HBVFE),  
PSA 9730 A8  
Renault DC4 DW5 (C6DCT 250 dry DCT9)  
Special Gear Oil, MTF 94  
Special Honda MTF/MTF-II  
Tranself TRT  
Volvo 97308/97309  
VW G 052 527 A2, G 070 726 A2,  
G 052 178  
VW G 052 512, G 052 726,  
VW G 060 726  
VW G 055 512 A2

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS GEAR OIL SAE 75W-80 SYNT

No. 15066

#### Description

- high performance low friction gear oil for lubrication of synchronized and nonsynchronized standard transmissions
- excellent high pressure- and wear protection properties
- very good properties in corrosion- and rust protection
- low foaming tendency and excellent aging stability
- high viscosity index and low pour point care for easy gear changing even at lot temperatures
- reduced oil consumption and extended oil drain intervals
- specially recommended for commercial vehicles with BMW, VW and Mercedes Benz manual transmissions

#### Specification / Recommendation

API GL-4  
BMW MTF LT-1/-2/-3/-4  
Fiat 9.55550-MZ6  
FORD WSS-M2C200-C/  
D2/+112C186-A  
GM 1940182/1940764/1940768  
MB 235.10  
NISSAN MT-XZ/MT-XZ TL (JR Type)  
PSA B 71 2330 (EZL\_848) +  
B71 2315  
Special Gear Oil, MTF 94  
Special Honda MTF/MTF-II/MTF-III  
Tranself NFJ, NFP, TRJ, TRT, TRZ,  
TRP, TRX  
Volvo 97308 / 97309  
VW G 009 317, VW G 052 171,  
G 052 178  
VW G 052 512, G 052 726,  
VW G 060 726  
VW G 50, G 052 527 A2,  
G 070 726 A2  
VW G052 549

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# MANUAL TRANSMISSION OILS

## OILERS GEAR OIL SAE 75W-90 SYNT TS-4

No. 15007

### Description

- synthetic ATF for double clutch transmission (DCT)
- developed for the latest generation of DCT
- extremely high wear resistance
- high thermal stability
- excellent viscosity
- good temperature behaviour
- low pour point
- foamless even under difficult conditions
- high oxidation stability
- carrying capacity
- optimum friction characteristics
- neutral to metals and sealing materials

### Specification / Recommendation

Audi/Volkswagen/Seat/Skoda -  
G 052 182 A2/A6 (TL 52 182),  
G 052 529 A2/A6 (TL 52 529),  
G 055 529 (TL 52 529-C)  
BMW -DCTF-1 (83 220 440 214),  
DCTF-1+, DCTF-2  
BMW 6-Speed DCT, MTF-LT-5  
(83 22 2167 666), 83 22 2 147 477,  
83 22 2 148 578, 83 22 2 148 579,  
83 22 2 446 673  
Citroen/Peugeot- 6DCT451  
(PSA 9734.S2)  
Ford WSS-M2C200-D2/ XT-11-QDC/  
WSS-M2C-936-A, part #  
1490763/1490761/ WSS-M2C218-  
1A, -F-DC, part # KU7J M2C218AA  
Ford/Nissan Powershift 6-Speed  
(GFT)  
Mercedes Benz - MB 236.5/236.21/  
236.22/236.24/239.21  
Mitsubishi - TC-SST 6-Speed (GFT),  
MZ320065 DiaQueen SSTF-1; DCT  
Transmission oil for ZF  
Porsche - 043 207 29, 043 207 30,  
000 043 20, 000 043 305 13, 999  
917 080 01, 000 043 210 44, 971  
094 307 02A  
Renault 77 11 785 243 (DW5) / EDC  
6-Speed (Getrag), EDC 7 /- BOT 450  
Volvo Powershift 6-Speed  
(GFT)/1161838/1161839  
VW G 052 536, 055 536; VW Audi  
G 052 512; VW (Audi, Seat, Skoda)  
6-Speed; Audi TL 52529/G 052 529  
A2/A6 (fluid) / DSG 7= S-tronic 7/  
7-Speed VW (Audi, Seat, Skoda);  
VW/Audi G 055 529 A1/A2/A6  
ZF TE-ML 11 (ZF004743), ZF  
Lifeguard Fluid 8.2  
for more specs please see TDS

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

**OILERS GEAR OIL SAE 75W-90 SYNT TS****No. 15008****Description**

- reducing the frictional resistance in gearing
- effective protection against early wear
- smooth running gear shifting at low temperatures
- lasting protection against corrosion and deposits
- total operational reliability at long using periods
- for highly loaded hypoid gears with great offset and for all-wheel drives
- manual gears, power dividers and intermediate gear boxes

**Specification / Recommendation**

API GL-5  
MAN 342 Typ M-1  
MB 235.0  
MIL-L-2105 D  
Volvo 97310  
ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B

**Packaging Units**

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

**OILERS GEAR OIL SAE 75W-90 SYNT LS-5****No. 15004****Description**

- outstanding oxidation stability
- extreme load-carrying capacity
- excellent anti-stick-slip characteristics
- enduring protection against corrosion and deposits
- special additivation for noise reduction
- for axle gears with self locking differentials in motor
- vehicles and commercial cars
- LS-gear oil - recommended for agriculture, forestry and construction industry
- suitable in hypoid gears without locking differential

**Specification / Recommendation**

API GL-5  
Arvin Meritor Axles  
Liebherr  
MAN 342 M1  
MB 235.0  
Volvo 97310  
ZF TE-ML 05C, 12C, 16E, 21C

**Packaging Units**

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

**OILERS GEAR OIL SAE 75W-90 SYNT****No. 15002****Description**

- fully synthetic high performance low friction gear oil
- covers the extreme high requirements of transaxle drives
- good gear operation at low temperatures
- excellent cold flow properties
- good synchronizing characteristics
- high ageing stability

**Specification / Recommendation**

API GL-4/GL-5/MT-1  
MAN 3343  
MAN M 342 M1/M2  
MB 235.6  
MIL-PRF-2105 D/E  
SAE J2360  
Scania STO 1:0  
Volvo STD 1273.21, 1273.10  
ZF TE-ML 02B, 05A, 07A, 08, 12E, 16B, 17A/B, 19B, 21A

**Packaging Units**

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# MANUAL TRANSMISSION OILS

## OILERS GEAR OIL SAE 80W-90

### Description

- multi grade EP gear oil
- excellent wear and corrosion protection / shear stability
- good cold flow properties
- high ageing stability
- low foaming tendency
- assured corrosion protection
- elastomer compatibility

### Specification / Recommendation

API GL-4  
MAN 341 E-1  
MB 235.1  
ZF TE-ML 06L, 08, 16A, 17A, 19A,  
19C, 24A

## No. 15001

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS GEAR OIL SAE 80W-90 GL-5

### Description

- specially designed gear oil for high-loaded hypoid gears with wide offset
- for power take-off gears, intermediate gears and secondary gears in motor vehicles and construction machines
- specially applies to rear axles with hypoid gearing
- good cold flow properties and high aging stability
- high shear stability and low foaming tendency
- assured corrosion protection and elastomer compatibility

### Specification / Recommendation

API GL-5  
MAN 342 M-2 (160.000 km oil change)  
MB 235.0  
MB 235.6  
MIL-L-2105 D  
ZF TE-ML 05A, 07A, 08, 12E, 16B-D,  
17B, 19B, 21A

## No. 15003

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS GEAR OIL SAE 80W-90 LS-5

### Description

- special gear oil for axle transmissions with Limited-Slip-Differentials
- assures optimal operation reliability and long lifetime of the aggregates to be lubricated
- outstanding oxidation stability
- extreme load-carrying capacity
- excellent anti-stick-slip characteristics
- endurable protection against corrosion and deposits
- special additivation for noise reduction

### Specification / Recommendation

API GL-5  
MAN 342 M1  
MB 235.0  
Volvo 97310  
ZF TE-ML 05C, 12C, 16E, 21C

## No. 15006

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS GEAR OIL SAE 80W-90 SYNT

**No. 15000**

#### Description

- high performance multi grade gear oil
- for synchronized and non-synchronized manual gears
- also for steering gears, transfer gears, normal / hypoid toothed axle drives, including rear axles with outer planetary gears
- high wear protection within whole operation temperature range
- good shifting characteristics
- assured corrosion protection
- excellent wear and corrosion protection

#### Specification / Recommendation

API GL-4/GL-5  
 Ford WSP-M2C197-A  
 MAN 3343 Typ M  
 MAN M342 M1/M2  
 MB 235.0  
 MB 235.6  
 MIL-L-2105D/E  
 SAE J2360  
 Scania STO 1:0  
 Volvo 1273.10, 1273.21  
 ZF TE-ML 01, 05A, 07A, 08, 12A, 12E, 16B/C, 17B, 19B, 21A

#### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

### OILERS GEAR OIL SAE 75W-90 SYNT LS-5

**No. 15005**

#### Description

- high performance multi grade gear oil
- for passenger cars, trucks, busses, off-road and farm equipment
- provides maximum wear protection
- especially designed for high-loaded hypoid / power take-off gears
- excellent wear and corrosion protection
- good gear noise absorption
- low foam tendency even at high speed
- high shear stability

#### Specification / Recommendation

PI GL-5  
 MAN 342 M-2 (160.000 km oil change)  
 MB 235.0  
 MB 235.6  
 MIL-L-2105 D  
 ZF TE-ML 05A, 07A, 08, 12E, 16B-D, 17B, 19B, 21A

#### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

### OILERS GEAR OIL SAE 75W-140 SYNT

**No. 15012**

#### Description

- fully synthetic special gear oil for axle transmissions with Limited-Slip-Differentials
- outstanding oxidation stability
- extreme load-carrying capacity
- excellent anti-stick-slip characteristics
- enduring protection against corrosion and deposits
- special additivation for noise reduction

#### Specification / Recommendation

API GL-5  
 BMW LS Rear Axles  
 Ford WSL-M2C192-A  
 MB 235.61  
 Nissan GTR limited slip axles  
 ZF TE-ML 05C, 12D, 16G, 21D

#### Packaging Units

1 l bottle  
 4 l canister  
 5 l canister  
 20 l pail  
 60 l drum  
 200 l drum

# MANUAL TRANSMISSION OILS

## OILERS GEAR OIL SAE 85W-140

### Description

- high performance multi grade gear oil
- for passenger cars, trucks, busses, off-road and farm machinery
- provides maximum wear protection
- especially designed for high-loaded hypoid / power take-off gears
- excellent corrosion protection
- good gear noise absorption
- low foam tendency even at high speed
- high shear stability
- low foaming tendency

### Specification / Recommendation

API GL-5  
MAN 342 M-2 (160.000 km oil change)  
MB 235.0  
MB 235.6  
MIL-L-2105 D  
ZF TE-ML 05A, 07A, 08, 12E, 16B-D, 17B, 19B, 21A

## No. 15016

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS GEAR OIL SAE 140

### Description

- high-performance, high-pressure gear oil made from carefully selected base oils and multifunctional additives
- suitable for axle drives and especially for heavily loaded hypoid gears where a gear oil according to API GL-5 is required
- high pressure absorption capacity
- high aging resistance
- reduction of operating noise
- minimization of wear
- good viscosity-temperature behavior
- compatibility with common sealing materials

### Specification / Recommendation

API GL-5  
MIL-L-2105 D

## No. 15116

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS LH-M PLUS

**No. 15501**

#### Description

- high performance special hydraulic fluid
- especially designed for central hydraulics, power-steerings, convertible top actuation, hydro pneumatic chassis and shock absorbers
- excellent viscosity and temperature behaviour
- high shear stability
- outstanding ageing and oxidation stability
- excellent anti-wear and anti-corrosion properties
- good sealing compatibility

#### Specification / Recommendation

DIN 51524 part 3  
ISO 7308  
FIAT 9.55597  
IVECO 18-1823  
NH 610 A  
PSA B71 2710  
SDFG OF1611S

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS GEAR OIL SAE 75W-90 SYNT LS-5

**No. 15502**

#### Description

- high performance special hydraulic fluid
- especially designed for central hydraulics, power-steerings, convertible top actuation, hydro pneumatic chassis and shock absorbers
- excellent viscosity and temperature behaviour
- high shear stability
- outstanding ageing and oxidation stability
- excellent anti-wear and anti-corrosion properties
- good sealing compatibility

#### Specification / Recommendation

Chrysler MS-1872  
Chrysler MS-5931, P/N 04883077  
Chrysler MS-9602, ATF+4  
DEXRON III  
DEXRON IID  
Ford M2C195-A  
GM P/N 89021184  
GM 9985010, P/N 1052884  
Hyundai / Kia PSF-3  
MB 236.3, P/N 000 989 88 03  
Mitsubishi PS Fluid  
Mitsubishi Diamond SPIII  
Nissan PSF-II  
Saab P/N (45) 30 09 800  
Subaru P/N K0209A0080  
Toyota PSF Type EH, P/N 008886-01

#### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

# HYDRAULIC- AND STEERING FLUIDS

## OILERS ZH-M PLUS F SYNT

No. 15509

### Description

- synthetic high performance special hydraulic
- especially designed for central hydraulics, power-steerings, convertible top actuation, hydro pneumatic chassis and shock absorbers
- excellent viscosity and temperature behaviour
- high shear stability
- outstanding ageing and oxidation stability
- excellent anti-wear and anti-corrosion properties
- good sealing compatibility

### Specification / Recommendation

Audi P/N G002000, G002012  
Chrysler MS-1872, MS-5931, P/N 04883077  
Chrysler MS-9602, ATF+4  
Chrysler MS-10838, P/N 05142893AA  
Ford M2C195-A, M2C204-A (end. temp. range)  
GM 9985010, P/N 1052884, GM 9985835, P/N 12345866 (cold climate)  
Hyundai/Kia PSF-3, PSF-4  
MB 236.3, P/N 000 989 88 03, MB 345.0, P/N 001 989 2403  
Mitsubishi PS Fluid, Diamond SP II  
Nissan PSF-II  
Saab P/N (45) 30 09 800, P/N 30 32 380  
Subaru P/N K0209A0080  
Toyota PSF Type EH, P/N 008886-01  
VW P/N G002000, P/N G002012  
Volvo P/N 1161529

### Packaging Units

1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS BRAKE FLUID DOT 4

#### Description

- high performance brake fluid
- fully synthetic glycol base
- for use in hydraulic brake and clutch system
- high oxidation and corrosion inhibitors

#### Specification / Recommendation

FMVSS 116, DOT 4  
ISO 4925 Class 4  
SAE J 1704

### No. 25119

#### Packaging Units

0.25 l bottle  
0.5 l bottle  
1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS BRAKE FLUID DOT 5.1

#### Description

- high performance brake fluid
- fully synthetic glycol base
- for use in hydraulic brake and clutch system
- high oxidation and corrosion inhibitors

#### Specification / Recommendation

FMVSS 116  
SAE J 1703  
SAE J 1704  
ISO 4925 Class 3, 4 & 5.1

### No. 25114

#### Packaging Units

0.25 l bottle  
0.5 l bottle  
1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS HLP 22

### Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

### Specification / Recommendation

DIN 51 524-2 (HM)  
AIST 126  
ASTM D 6158 (HM)  
Bosch Rexroth RDE 90235  
Eaton E-FDGN-TBoo2-E  
Fives P68, P69, P70 (HM)  
GB 111158.1-2011 (L-HL, L.HM)  
GM LS-2  
ISO 11158 (HM)  
JCMAS P041 HK Hydraulic specification  
Parker (Denison) HF-0, HF-1, HF-2 (HM)  
SAE MS 1004 (HM)  
SEB 181222

## No. 13004

### Packaging Units

20 l pail  
60 l drum  
200 l drum

## OILERS HLP 32

### Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

### Specification / Recommendation

DIN 51 524-2 (HM)  
AIST 126  
ASTM D 6158 (HM)  
Bosch Rexroth RDE 90235  
Eaton E-FDGN-TBoo2-E  
Fives P68, P69, P70 (HM)  
GB 111158.1-2011 (L-HL, L.HM)  
GM LS-2  
ISO 11158 (HM)  
JCMAS P041 HK Hydraulic specification  
Parker (Denison) HF-0, HF-1, HF-2 (HM)  
SAE MS 1004 (HM)  
SEB 181222

## No. 13005

### Packaging Units

20 l pail  
60 l drum  
200 l drum

### OILERS HLP 46

#### Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

#### Specification / Recommendation

DIN 51 524-2 (HM)  
AIST 126  
ASTM D 6158 (HM)  
Bosch Rexroth RDE 90235  
Eaton E-FDGN-TBoo2-E  
Fives P68, P69, P70 (HM)  
GB 111158.1-2011 (L-HL, L.HM)  
GM LS-2  
ISO 11158 (HM)  
JCMAS P041 HK Hydraulic specification  
Parker (Denison) HF-0, HF-1, HF-2 (HM)  
SAE MS 1004 (HM)  
SEB 181222

### No. 13006

#### Packaging Units

0.25 l bottle  
0.5 l bottle  
1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

### OILERS HLP 68

#### Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

#### Specification / Recommendation

DIN 51 524-2 (HM)  
AIST 126  
ASTM D 6158 (HM)  
Bosch Rexroth RDE 90235  
Eaton E-FDGN-TBoo2-E  
Fives P68, P69, P70 (HM)  
GB 111158.1-2011 (L-HL, L.HM)  
GM LS-2  
ISO 11158 (HM)  
JCMAS P041 HK Hydraulic specification  
Parker (Denison) HF-0, HF-1, HF-2 (HM)  
SAE MS 1004 (HM)  
SEB 181222

### No. 13007

#### Packaging Units

0.25 l bottle  
0.5 l bottle  
1 l bottle  
4 l canister  
5 l canister  
20 l pail  
60 l drum  
200 l drum

## OILERS HLP 100

**No. 13008**

### Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

### Specification / Recommendation

DIN 51 524-2 (HM)  
AIST 126  
ASTM D 6158 (HM)  
Bosch Rexroth RDE 90235  
Eaton E-FDGN-TBoo2-E  
Fives P68, P69, P70 (HM)  
GB 111158.1-2011 (L-HL, L.HM)  
GM LS-2  
ISO 11158 (HM)  
JCMAS P041 HK Hydraulic specification  
Parker (Denison) HF-0, HF-1, HF-2 (HM)  
SAE MS 1004 (HM)  
SEB 181222

### Packaging Units

20 l pail  
60 l drum  
200 l drum

### OILERS ANTIFREEZE

**No. 11017**

#### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / concentrated
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

#### Specification / Recommendation

ASTM D 3306  
SAE J 1034  
AS 2108-2004  
AFNOR NF R15-601  
BS 6580:2010

#### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE G

**No. 11018**

#### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / concentrated
- especially designed to fulfill the requirements cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

#### Specification / Recommendation

ASTM D 3306  
SAE J 1034  
AS 2108-2004  
AFNOR NF R15-601  
BS 6580:2010

#### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE READY MIX -5°C

**No. 11175**

#### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

#### Specification / Recommendation

ASTM D3306  
ASTM D4985  
SAE J 1034  
BS 6580  
AFNOR NF R 15-601 TYPE 1  
AS 2108  
CUNA NC 956-16  
JIS K 2234  
ÖNORM V 5123  
UNE 26361

#### Packaging Units

1.5 l bottle  
5 l canister

# RADIATOR ANTIFREEZE / COOLANTS

## OILERS ANTIFREEZE READY MIX -5°C G

**No. 11185**

### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

### Specification / Recommendation

ASTM D3306  
ASTM D4985  
SAE J 1034  
BS 6580  
AFNOR NF R 15-601 TYPE 1  
AS 2108  
CUNA NC 956-16  
JIS K 2234  
ÖNORM V 5123  
UNE 26361

### Packaging Units

1.5 l bottle  
5 l canister

## OILERS ANTIFREEZE READY MIX -25°C

**No. 11041**

### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

### Specification / Recommendation

ASTM D 3306  
SAE J 1034  
AS 2108-2004  
AFNOR NF R15-601  
BS 6580:2010

### Packaging Units

1.5 l bottle  
5 l canister

## OILERS ANTIFREEZE READY MIX -25°C G

**No. 11042**

### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

### Specification / Recommendation

ASTM D 3306  
SAE J 1034  
AS 2108-2004  
AFNOR NF R15-601  
BS 6580:2010

### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE READY MIX -38°C

**No. 11051**

#### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

#### Specification / Recommendation

ASTM D 3306  
SAE J 1034  
AS 2108-2004  
AFNOR NF R15-601  
BS 6580:2010

#### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE READY MIX -38°C G

**No. 11052**

#### Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

#### Specification / Recommendation

ASTM D 3306  
SAE J 1034  
AS 2108-2004  
AFNOR NF R15-601  
BS 6580:2010

#### Packaging Units

1.5 l bottle  
5 l canister

# RADIATOR ANTIFREEZE / COOLANTS

## OILERS ANTIFREEZE 12 PLUS

**No. 11014**

### Description

- long life radiator antifreeze, anti-corrosion and coolant
- all year use / concentrated
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

### Specification / Recommendation

VW TL 774 D, VW TL 774 F  
MAN 324 SNF  
MB 325.3  
Ford WSS-M97B44-D  
GM 6277M  
AS 2108-2004  
ASTM D 3306, ASTM D 4985  
AFNOR NF R15-601  
BS 6580:2010  
SAE J 1034

### Packaging Units

1.5 l bottle  
5 l canister

## OILERS ANTIFREEZE READY MIX 12 PLUS -5°C

**No. 11145**

### Description

- long life radiator antifreeze, anti-corrosion and coolant
- all year use / concentrated
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

### Specification / Recommendation

ASTM D3306  
ASTM D4985  
SAE J 1034  
MB 325.3  
Opel GM QL 130100  
JIS K 2234, JASO M325  
AUDI, SEAT, SKODA  
VW TL 774 F (G12+)  
VW TL 774 D (G12)  
ISUZU  
RENAULT 41-01-001/-S Type D  
GM 1899 M  
MAZDA  
Volvo  
for more specs please see TDS

### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE READY MIX 12 PLUS -25°C

No. 11048

#### Description

- long life radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

#### Specification / Recommendation

VW TL 774 D, VW TL 774 F  
MAN 324 SNF  
MB 325.3  
Ford WSS-M97B44-D  
GM 6277M  
AS 2108-2004  
ASTM D 3306, ASTM D 4985  
AFNOR NF R15-601  
BS 6580:2010  
SAE J 1034

#### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE READY MIX 12 PLUS -37°C

No. 11049

#### Description

- long life radiator antifreeze, anti-corrosion and coolant
- all year use / ready to use for radiator
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

#### Specification / Recommendation

VW TL 774 D, VW TL 774 F  
MAN 324 SNF  
MB 325.3  
Ford WSS-M97B44-D  
GM 6277M  
AS 2108-2004  
ASTM D 3306, ASTM D 4985  
AFNOR NF R15-601  
BS 6580:2010  
SAE J 1034

#### Packaging Units

1.5 l bottle  
5 l canister

# RADIATOR ANTIFREEZE / COOLANTS

## OILERS ANTIFREEZE G013

**No. 11013**

### Description

- long life radiator antifreeze, anti-corrosion and coolant
- all year use / concentrated
- fulfills the VW-specification VW TL 774-F (G13)
- free from nitrites, amines and phosphonates
- provides reliable protection for aluminium and cast iron engines
- backward compatible to G12++ and G12+ (TL 774 G/F) prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

### Specification / Recommendation

VW TL 774 J  
Audi  
Bentley  
Lamborghini  
Seat/Skoda

### Packaging Units

1.5 l bottle  
5 l canister

## OILERS ANTIFREEZE G013 READY MIX -5°C

**No. 11135**

### Description

- long life radiator antifreeze, anti-corrosion and coolant
- all year use / concentrated
- fulfills the VW-specification VW TL 774-F (G13)
- free from nitrites, amines and phosphonates
- provides reliable protection for aluminium and cast iron engines
- backward compatible to G12++ and G12+ (TL 774 G/F) prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

### Specification / Recommendation

ASTM D 3306  
AUDI, (BENTLEY,  
BUGATTI, LAMBORGHINI),  
SEAT, SKODA G 13  
VW TL 774 J

### Packaging Units

1.5 l bottle  
5 l canister

### OILERS ANTIFREEZE G013 READY MIX -35°C

**No. 11061**

#### Description

- long life radiator antifreeze, anti-corrosion and coolant
- ready to use for -35°C / all year use
- fulfills the VW-specification VW TL 774-F (G13)
- free from nitrites, amines and phosphonates
- provides reliable protection for aluminium and cast iron engines
- backward compatible to G12++ and G12+ (TL 774 G/F) prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

#### Specification / Recommendation

VW TL 774 J  
Audi  
Bentley  
Lamborghini  
Seat/Skoda

#### Packaging Units

1.5 l bottle  
5 l canister

## OILERS OCTANE BOOSTER

### Description

- high quality additive for gasoline engines
- improves octane number up to 7 points
- maximum engine performance
- excellent acceleration of engine
- for 70L gasoline
- lowers fuel consumption

**No. 12110**

**Packaging Units**

300 ml metal can

## OILERS CETANE BOOSTER

### Description

- high quality additive for diesel engines
- improves cetan number and ignition quality
- maximum engine performance
- plus special purification additive
- lowers fuel consumption

**No. 12120**

**Packaging Units**

300 ml metal can

## OILERS INJECTION CLEANER

### Description

- high quality additive for injection system
- made for gasoline engines
- top cleanliness properties against deposit
- excellent protection against corrosion
- for 60L gasoline
- very good anti-sludge properties

**No. 12130**

**Packaging Units**

300 ml metal can

## OILERS ENGINE FLUSH

- high quality additive to clean engine
- 300ml made for 6L oil in gasoline or diesel engines
- highly effective detergent and dispersant
- dissolve sludge and dirt
- optimal engine cleanliness

**No. 12140**

300 ml metal can

### OILERS RADIATOR LEAK STOP

#### Description

- high quality additive for radiators
- suitable for all types of radiators
- stops leakages very fast
- long time sealing behaviour
- excellent anticorrosion agent
- compatible to all types of coolants

**No. 12150**

**Packaging Units**

300 ml metal can

### OILERS ANTI SMOKE

#### Description

- high quality additive for diesel engines
- maximum engine performance
- increases engine power and engine life
- provide the self-cleaning of the DPF
- for 80 L diesel
- lowers fuel consumption

**No. 12160**

**Packaging Units**

300 ml metal can

### OILERS DPF CLEANER

#### Description

- high-quality additive for diesel engines to reduce sludge formation
- created especially for cleanliness of the DPF
- optimizes engine power and life time of the DPF
- regular application is recommended.

**No. 12170**

**Packaging Units**

300 ml metal can

### OILERS RADIATOR CLEANER

#### Description

- high-quality additive for clean out the entire cooling system removes corrosion and sludge deposits

**No. 12180**

**Packaging Units**

300 ml metal can

### OILERS DIESEL SYSTEM CLEANER

#### Description

- high-quality additive for cleaning of nozzles and valves of diesel engines
- optimizes the engine power and extends the life time of the engine

**No. 12190**

**Packaging Units**

300 ml metal can

## OILERS OIL TREATMENT

### Description

- high-quality additive to improve the viscosity of motor oils
- improves sealing and reduces oil consumption and engine wear
- suitable for gasoline and diesel engines with catalyst, diesel particulate filter and turbocharger

**No. 12200**

**Packaging Units**

300 ml metal can

## OILERS CATALYST CLEANER

### Description

- high-quality additive to protects the catalyst against sludge deposits
- inlet valves and combustion chamber will be cleaned
- fuel system will be protected against corrosion
- reduces the CO2 emissions and protects the environment

**No. 12215**

**Packaging Units**

300 ml metal can

### **GERMAN OILERS**

Vogelweidstraße 8  
60596 Frankfurt am Main  
GERMANY

Phone: +49 69 697 692 10  
[export@germanoilers.com](mailto:export@germanoilers.com)  
[www.germanoilers.com](http://www.germanoilers.com)



We are not reliable for any mistakes in this catalog.



## PACKAGING FOR CONTAINERS

0.3 l bottle	2184 / 2688	piece / pallete =	91 / 112 cartons
0.4 l bottle	2160	piece / pallete =	180 cartons
0.5 l bottle	1920	piece / pallete =	160 cartons
1 l bottle	1176	piece / pallete =	98 cartons
1.5 l bottle	672	piece / pallete =	56 cartons
4 l canister	336	piece / pallete =	84 cartons
5 l canister	270	piece / pallete =	90 cartons
10 l canister	60	piece / pallete	
20 l pail	90	piece / pallete	
25 l pail	75	piece / pallete	
60 l drum	9x2	piece / pallete	
200 l drum	4x2	piece / pallete	
1000 l IBC	2	piece / pallete	

### Brake Fluid

0.25 l bottle	2340	piece / pallete =	195 cartons
0.5 l bottle	1680	piece / pallete =	100 cartons
1 l bottle	1020	piece / pallete =	136 cartons

### Container loading

20' container	10 pallets/container
40' container	20 pallets/container

## PACKAGING FOR TRUCKS

max. loading 22,500 kg

0.3 l bottle	1680 / 2016	piece / pallete =	70 / 84 cartons
0.4 l bottle	2160	piece / pallete =	180 cartons
0.5 l bottle	1920	piece / pallete =	160 cartons
1.5 l bottle	672	piece / pallete =	56 cartons
4 l canister	200	piece / pallete =	50 cartons
5 l canister	150	piece / pallete =	50 cartons
20 l pail	30	piece / pallete	
25 l pail	30	piece / pallete	
60 l drum	6x2	piece / pallete	
200 l drum	4x2	piece / pallete	
1000 l IBC	1	piece / pallete	

### Brake Fluid

0.25 l bottle	2340	piece / pallete =	135 cartons
0.5 l bottle	1680	piece / pallete =	70 cartons
1 l bottle	1020	piece / pallete =	102 cartons

**Pallets only stackable for container loading.  
Not available for truck shipment!**

# OILERS

GERMAN

Version 09/2025



# MADE IN GERMANY

GERMAN OILERS, Vogelweidstraße 8, Frankfurt, GERMANY, [www.germanoilers.com](http://www.germanoilers.com)